## Mobile Airport Authority

MAA TERMINAL RELOCATION Mobile, Alabama



BID PACKAGE #1 - DEMOLITION AND ASBESTOS ABATEMENT 100% BID SUBMISSION AUGUST 18, 2023




REGISTRATION NO.

Nick Rose DATE 08-18-2023 PROJECT MANAGER PE No. 51304










SHEET NO.	DESCRIPTION	SHEET NO.	DESCRIPTION
1	TITLE SHEET	4	DEMOLITION PLAN SHEET
1A	INDEX TO SHEETS	5	ULTIMATE PROJECT LAYOUT SHEET
1B	PLANS LEGEND/STANDARD AND SPECIAL DRAWINGS SHEET	6-9	OMITTED
1C	PLANS ABBREVIATIONS SHEET	10	EXISTING UTILITY SHEET
2	SAFETY NOTES SHEET	11-14	OMITTED
2A	CONSTRUCTION SAFETY PHASING PLAN SHEET	15	TRAFFIC CONTROL PLAN
2B-2C	PROJECT NOTES SHEET	15A-15B	TRAFFIC CONTROL PLAN - DETAILS
2D-2E	TRAFFIC CONTROL PLAN NOTES SHEET	16-19	OMITTED
3	SUMMARY OF QUANTITIES SHEET	20	EROSION CONTROL PLAN - LEGEND
3A-3B	BOX SUMMARY SHEET	20A	EROSION CONTROL PLAN

#### INDEX TO SPECIAL AND STANDARD DRAWINGS


THE FOLLOWING ARE SPECIAL OR STANDARD DRAWINGS CONTAINED IN THE ALABAMA DEPARTMENT OF TRANSPORTATION SPECIAL AND STANDARD HIGHWAY DRAWINGS BOOK (U.S. CUSTOMARY UNITS OF MEASUREMENTS) DATED 2023 WHICH APPLY TO THIS PROJECT.

INDEX NO	STD-DWG NO	DESCRIPTION	INDEX NO	STD-DWG NO	DESCRIPTION
66501	ESC-100-1	BEST MANAGEMENT PRACTICE REFERENCE MATRIX	66518	ESC-300-7	DETAILS OF ROCK DITCH CHECKS WITH SUMP EXCAVATION
66502	ESC-100-2	BEST MANAGEMENT PRACTICE REFERENCE MATRIX	66519	ESC-300-8	DETAILS OF SILT FENCE DITCH CHECKS
66505	ESC-200-1	TYPICAL TEMPORARY EROSION / SEDIMENT CONTROL APPLICATIONS	66522	ESC-400-1	INLET PROTECTION TYPICAL APPLICATIONS AND DETAILS
66507	ESC-200-3	DETAILS OF SEDIMENT BARRIER APPLICATIONS	66523	ESC-400-2	INLET PROTECTION DETAILS FOR COARSE AGGREGATE ON GRADES AND SAGS
66508	ESC-200-4	DETAILS OF SILT FENCE INSTALLATION	66524	ESC-400-3	INLET PROTECTION DETAILS OF SUIT FENCE
66509 66512	ESC-200-5 ESC-300-1	DETAILS OF SEDIMENT RETENTION BARRIER  DITCH CHECK STRUCTURES, TYPICAL APPLICATIONS AND DETAILS	66525 66526	ESC-400-4 ESC-400-5	INLET PROTECTION DETAILS OF SILT FENCE  INLET PROTECTION DETAILS OF SAND BAGS
66513	ESC-300-2	DETAILS OF HAY BALE DITCH CHECKS	66532	ESC-502	STABILIZED CONSTRUCTION ENTRANCE
66514	ESC-300-3	DETAILS OF SANDBAG DITCH CHECK	74001	B-107-2	PERFORATED SQUARE STEEL TUBING (PSST) BARRICADES TYPE I,
66515	ESC-300-4	DETAILS OF EROSION CONTROL WATTLE DITCH CHECKS	74004	LCS-107	TYPE II, AND TYPE III & VERTICAL PANELS TYPE I AND TYPE II  DETAILS SHOWING REQUIREMENTS FOR LIGHTING CONSTRUCTION SIGNS
66516	ESC-300-5	DETAILS OF SILT DIKE DITCH CHECKS	74007	TCD-100	DETAILS OF TRAFFIC CHANNELIZATION DEVICES
66517	ESC-300-6	DETAILS OF ROCK DITCH CHECKS			









Nobile Airport Authority
NAA TERMINAL
RELOCATION

Alabama

REVISIO	ON HISTORY	
	DESCRIPTION	DATE
PROJEC	CT INFORMATION	
DEGLON	IED DV:	

Δ	DESCRIPTION	DATE
PROJEC	CT INFORMATION	•
DESIGN	ED BY:	·
JNR		DSG
DRAWN	BY:	
JNR		DRN
REVIEW	/ED BY:	
HZE		CHK
PROJEC	CT MANAGER:	
JNR		DOG
PROJEC	T NUMBER	•

PROJECT NUMBER 1149211

SHEET TITLE:

INDEX TO SHEETS

ISSUE DATE

17 August, 2023
SHEET NUMBER

1A

#### ROADWAY

	55+00
CENTER LINE	<del></del>
STATE BOUNDARY LINE	
COUNTY BOUNDARY LINE	·
CITY OR TOWN LIMITS	SEC 22
SECTION LINES	SEC 23
QUARTER-SECTION LINES	
PROPERTY LINES	
PRESENT ROW	`
ACQUIRED ROW	
DENIED ACCESS	
REQUIRED FENCE	xx
	CONST LIM
CONSTRUCTION LIMITS	
RAILROAD	
EXISTING WOOD FENCE	
EXISTING BARBED WIRE FENCE	x
EXISTING CHAIN LINK FENCE	<del></del>
EXISTING ELECTRIC FENCE	——е ——е
EXISTING HOG WIRE FENCE	——————————————————————————————————————
TREES	$\odot$ $\odot$ $\odot$
WOODS LINE	
MARSH	
EXISTING DITCH	
REQUIRED DITCH	
GRAVEL ROAD	= = = = = = =
EXISTING GUARDRAIL	<u>.                                    </u>
REQUIRED GUARDRAIL	<u> </u>
SATELLITE DISH	
TRAFFIC LIGHT	EME.
BENCH MARK	
SURVEY POINT	+
ENVIRONMENTAL CLEARED LIMITS	ENV

EXISTING PIPE	H
REQUIRED PIPE	
(WITH PIPE END TREATMENT)	
REQUIRED PIPE END TREATMENT	
EXISTING BOX CULVERT	) J=====
	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
REQUIRED BOX CULVERT	
EXTENDED CULVERT	<b>=</b> = = <b>=</b>
DROP INLET OR JUNCTION BOX	
(SEE PLANS DESCRIPTION )	
BRIDGE	
DINIDOL	
PIPE CULVERT (ELEVATION VIEW)	
THE GOLVERY (LLEVYTHON VIEW)	\ }=410.25
BOX CULVERT (ELEVATION VIEW)	
DOX COLVERT (LLL V/TION VILVV)	Щ
	`}=420.55

#### DRAINAGE STRUCTURE INDEX NUMBERS

DRAINAGE STRUCTURE WRITE-UPS ARE LOCATED ON THE DRAINAGE CROSS-SECTION SHEETS. STRUCTURES WITH WRITE-UPS ARE INDEXED AT EACH END, WITH NUMBERS ASSIGNED BY DIRECTION OF FLOW. THE NUMBER IN THE UPPER HALF OF THE CIRCLE (EXAMPLE 8 OR 9) IS THE DRAINAGE STRUCTURE INDEX NUMBER. THE NUMBER IN THE LOWER HALF (EXAMPLE 88) IS THE SHEET REFERENCE NUMBER.



ROADWAY PIPE EXAMPLE

ALL INFORMATION CONCERNING THE DISPOSITION OF SIDE DRAIN PIPE IS SHOWN ON THE SUMMARY OF QUANTITIES BOX SHEET. THE TOP LETTERS (SD) ARE FOR SIDE DRAIN AND THE BOTTOM NUMBER IS THE DRAINAGE STRUCTURE INDEX NUMBER.



DIRECTION OF FLOW .....

#### UTILITIES


	EXISTING	PROPOSED
POWER POLE		
LIGHT POLE		-
TELEPHONE POLE	$\overline{}$	-
ANCHOR	$\triangle$	
STUB (POWER)		
STUB (TELEPHONE)	<del>-</del>	•
ELECTRIC DUCT	===== EL 4MTD =====	===== EL 4MTD ======
BURIED ELECTRIC CABLE	— — — — — BE — — — — —	———— BE ————
OVERHEAD ELECTRIC CABLE		OE
ELECTRIC MANHOLE	======================================	
TOWER		$\bowtie$
TELEPHONE PEDESTAL		T
TELEPHONE DUCT	= $=$ $=$ TP 4MTD $=$ $=$ $=$	TP 4MTD
BURIED TELEPHONE CABLE	———— BTC ————	——— ВТС———
OVERHEAD TELEPHONE CABLE	otc	<u>otc</u>
TELEPHONE MANHOLE	= = = = = TMH= = = = =	ТМН
SANITARY SEWER	s	SS
WATER LINE	w	———— W ————
WATER MAIN		WM
WATER VALVE		$\triangle$
FIRE HYDRANT	$\ominus$	
WATER METER	$\boxtimes$	
GAS LINE	G	———— G ————
GAS MAIN		GM
GAS VALVE	G	A
GAS REGULATOR	0	•
BURIED CABLE TELEVISION	BTV	———— BTV ————
OVERHEAD CABLE TELEVISION	OTV	OTV

EXISTING PAVEMENT (RETAIN)	
EXISTING PAVEMENT (REMOVE)	
EXISTING PAVEMENT (RETAIN AND OVERLAY)	
CONCRETE (EXISTING OR REQUIRED)	
EXISTING CONCRETE (REMOVE)	
RIP RAP (EXISTING OR REQUIRED)	
EXISTING GRAVEL (RETAIN)	
EXISTING GRAVEL (REMOVE)	









### Authority TERMINAL le Airport WAA TERMINA RELOCATION lobil

Alabama

REVISION HISTORY
△ DESCRIPTION DATE
PROJECT INFORMATION
DESIGNED BY:

DSG JNR DRAWN BY: JNR DRN REVIEWED BY: CHK HZE PROJECT MANAGER: DOG PROJECT NUMBER 1149211

PLANS LEGEND SHEET

ISSUE DATE 17 August, 2023

SHEET TITLE:

SHEET NUMBER

1B

BANDON(ED) BUTMENT	ABAN ABUT	FORESIGHT OR FRONTSIGHT FRACTIONAL	FRAC
CCELERATION	ACCL	FULL SUPERELEVATION	FS
CQUIRED CRE	ACQD AC	GALLONGASOLINE PUMPS	
HEAD LABAMA		GARAGEGAUGE	GAR
LABAMA DEPARTMENT OF TRANSPORTATION	ALDOT	GIRDER	GDR
LTERNATE PPROXIMATE(LY)		GOVERNMENTGRASS	GRS
REASPHALT	Α	GRADE CHANGEGRADE POINT	GC
VERAGE ANNUAL DAILY TRAFFIC	AADT	GRADE ROD	GRD
ACK OF GUARDRAIL	BK-GR	GRAVEL GUARDRAIL	GR
ACKSIGHT ARBED WIRE	BS	HEADWALL	HDW
\RREL	BBL	HECTAREHIGH WATER MARK	HWM
ARRIER ASE LINE		HEIGHT HEIGHT OF INSTRUMENT	······ HT
ARINGGIN	BRNG	HIGH WATER	HW
GINNING OF PROJECT	BOP	HIGHWAY HOGWIRE	H/W/
TWEEN _LBOARD		HORIZONTALHUB & TACK	············· HOR
NCH MARK FUMINOUS	BM	HYDRANT	HYD
FUMINOUS COATED CORRUGATED METAL PIPE	.BCCMP	IMPACT ATTENUATORIN ACCORDANCE WITH	Ï/À/W
UNDARYIDGE	BRG	IN PLACEINCHES	IN-PL
IDGE END SLABPACITY	BES	INCLUDING	······ INCI
ST IRON	CI	INCORPORATEDINSTRUMENT	INST
ST IN PLACE TCH BASIN	CB	ISLAND JOINT	ISI
NTER LINEAIN LINK	1	JUNCTION	JCT
ASS	. CLS	JUNCTION BOXKILOMETER	KM
NCRETE NNECTION	CONN	KILOMETER POSTKILOMETERS PER HOUR	KMP
NSTRUCTION LIMITSRNER	CONST LIM	LANE	LN
RRECTION	CORR	LATITUDE LEFT	LAT
RRUGATED IRONRRUGATED METAL	CM	LEFT AHEADLEFT BACK	LA
RRUGATED METAL PIPERUGATED PLASTIC PIPE	CMP	LENGTH OF CURVE	L
UNTY	CO	LINKLINKLINK	
JNTY ROAD EEK		LINEAR	LIN
OSS SECTION OWN REMOVED		LINEAR FEET LONGITUDE	LONG
BIC FEET	FT3 or CU FT	MANHOLE MARKER	MH MRK
BIC FEET PER SECOND BIC YARD	. YD3 or CU YD	MAXIMUM	MAX
BIC METERS _VERT	M3	MEAN HIGH WATER MEAN LOW WATER	MLW
_TIVATED	CULT	MEASUREMENT MEDIAN	MEA
RB FACE RB AND GUTTER	CF C&G	METER	M
T RVE TO SPIRAL		MERIDIAN MILE POST	MP
CELERATION	DECEL	MILES MILES PER HOUR	MI MPH
CLINATIONGREE OF CURVE	D	MILLIMETER	MM
NIED ACCESS PARTURE	D/A DEP	MINIMUM MONUMENT	MON
METER	DIA	MULTIPLE NORMAL	MUL NOR
ECTIONTANCE	DIST	NORMAL CROWN	NC
UBLEUBLE BARREL CULVERT	DBL CD	NORMAL CROWN SLOPENORTH	N
AINAGE AREA	DA	NORTH BOUND ROADWAY NORTHING-EASTING	
VE DP INLET	DI	NOT IN CONTRACT	NIC
CH SEMENT		NOT TO SCALENUMBER	
ST	E	OBSERV ON CENTER	OBS
ST BOUND ROADWAY GE OF PAVEMENT		ORIGINAL	ORIG
EVATION D OF RETURN	EL or ELEV	OVERHEAD OVERHAUL	
D ANCHOR	E/A	OUT TO OUT	00
D OF PROJECTUATION	EQ	PAINTPAVED	PVD
OSION CONTROL PRODUCTS	ECP	PAVED SHOULDER PAVEMENT	
STING	EX	PIPE END TREATMENT	PET
PANSION TENSION		PIPE ENTERING CULVERT PLATE GIRDER	PL G
TERNALTRA STRENGTH	Ē	POINT OF BEGINNINGPOINT OF COMPOUND CURVE	POB
T	FT	POINT OF CURVATURE	PC
L TER BLANKET		POINT OF REVERSE CURVATURE POINT OF ENDING	
ISHED GRADE	FG	POINT OF INTERSECTION	PI
ISHED SURFACE CAL YEAR	FY	POINT OF TANGENCYPOINT ON CURVE	POC
ED AT BOTTOM	FIX	POUNDPRESENT	LB
OW LINE		PROFILE GRADE	

PROJECT	
	PROJ
PROJECT CONTROL	PJC
PROPERTY LINE	
PROPOSEDQUADRUPLE	
QUADRUPLE BARREL CULVERT	CO
QUANTITY	
RADIUS	
RAILROAD	
RANGERECORD	
REDUCTION	
REFERENCE	REF
REFERENCE POINT	RP
REFERENCE POINT FOR POINT ON TANGENT	
REINFORCEDREINFORCED CONCRETE	REINF
REINFORCED CONCRETE DECK GIRDER	RCDG
REINFORCED CONCRETE PIPE	
REINFORCING STEEL	
RELOCATE	
REMOVE	
REQUIREDRETAIN(ING)	
REVERSE CROWN	RC
REVISION	.REV
RIGHT	.RT
RIGHT AHEAD	. RA
RIGHT DE WAY	. KB ROW
RIGHT OF WAYRIGHT OF WAY MARKER	ROWM
RIVER	.RIV
ROAD	.RD
ROADWAY	
SECTIONSERVICE ROAD	
SHEET	SHT
SHEET PILING	SHT PILE
SHOULDER	SHLD
SIDE DRAIN	SD
SIDEWALKSIGHT DISTANCE	SW
SINGLE BARREL CULVERT	S DIST
SKEW	SK
SKEWSLOPE STAKE	SST
SOLID SODDING	SOL SOD
SOUTHSOUTH BOUND ROADWAY	S
SPECIAL	SP
SPECIAL DITCH	SP-DT
SPECIAL DITCH LEFT	SDL
SPECIAL DITCH MEDIAN	.SDM
SPECIAL DITCH RIGHTSPECIAL DRAWING	SD-DWG
SPECIFICATIONS	SPFC
SPRING LINE	SL
SPRING LINESPIRAL TO CURVE	SC
SPIRAL POINT OF INTERSECTION	SPI
SPIRAL TO TANGENT	SO
SQUARESQUARE FEET	FT2 or SQ FT
SQUARE METERS	M2
SQUARE YARD	
STAKESTANDARD	
	CTD DWC
STANDARD DRAWING	ション・コン・フィン・フィン・フィン・フィン・フィン・フィン・フィン・フィン・フィン・フィ
STANDARD DRAWINGSTANDARD STRENGTH	STD STR
STANDARD STRENGTHSTATION	STD STR STA
STANDARD STRENGTHSTATIONSTATION & ELEVATION	STD STR STA .S/E
STANDARD STRENGTHSTATIONSTATION & ELEVATION	STD STR STA .S/E
STANDARD STRENGTHSTATIONSTATION & ELEVATIONSTATION & OFFSETSTOPPING SIGHT DISTANCE	STD STR STA .S/E .SO .SSD
STANDARD STRENGTHSTATIONSTATION & ELEVATIONSTATION & OFFSETSTOPPING SIGHT DISTANCE	STD STR STA .S/E .SO .SSD .ST
STANDARD STRENGTHSTATIONSTATION & ELEVATIONSTATION & OFFSETSTOPPING SIGHT DISTANCESTREETSTRUCTURESUB-GRADE	STD STR STA .S/E .SO .SSD .ST .STR .SG
STANDARD STRENGTH	STD STR STA .S/E .SO .SSD .ST .STR .SG .SE,se or e
STANDARD STRENGTH	STD STR STA .S/E .SO .SSD .ST .STR .SG .SE,se or e .SRV
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT	STD STR STA .S/E .SO .SSD .ST .STR .SG .SE,se or e .SRV .SYM
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA).	STD STR STA .S/E .SO .SSD .STR .SG .SE,se or e .SRV .SYM .TAN
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL	STD STR STA .S/E .SO .SSD .STR .SG .SE,se or e .SRV .SYM .TAN .T
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL	STD STR STA .S/E .SO .SSD .STR .SG .SE,se or e .SRV .SYM .TAN .T
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK	STD STR STA .S/E .SO .SSD .ST .STR .SG .SE,se or e .SRV .SYM .TAN .T .TS TEMP
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK THROAT	STD STR STA .S/E .SO .SSD .ST .STR .SG .SE,se or e .SRV .SYM .TAN .T .TS TEMP TBM
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK THROAT TOWNSHIP	STD STR STA .S/E .SO .SSD .STR .SG .SE,se or e .SRV .TAN .TAN .T .TS TEMP TBM TH
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK THROAT TOWNSHIP TRIPLE TRIPLE BARREL CULVERT	STD STR STA .S/E .SO .SSD .ST .STR .SG .SE,se or e .SRV .SYM .TAN .T .TS .TEMP .TBM .TH .TSHP .TSHP
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK THROAT TOWNSHIP TRIPLE TRIPLE BARREL CULVERT	STD STR STA .S/E .SO .SSD .ST .STR .SG .SE,se or e .SRV .SYM .TAN .T .TS .TEMP .TBM .TH .TSHP .TSHP
STANDARD STRENGTH STATION STATION & ELEVATION. STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY BENCH MARK THROAT TOWNSHIP TRIPLE TRIPLE BARREL CULVERT TURN OUT TURNING POINT	STD STR STA .S/E .SO .SSD .STR .SG .SE,se or e .SRV .TAN .TAN .T .TBM .TBM .TH .TSHP .TBM .TH .TSHP .TTR
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK THROAT TOWNSHIP TRIPLE TRIPLE TRIPLE BARREL CULVERT TURN OUT TURNING POINT TYPE UNIT	STD STR STA .S/E .SO .SSD .STR .SG .SE,se or e .SYM .TAN .T .TS .TEMP .TBM .TBM .TBM .TBM .TBM .TBM .TSHP .TSHP .TY .TY
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK THROAT TOWNSHIP TRIPLE TRIPLE BARREL CULVERT TURN OUT TURNING POINT TYPE UNIT UNKNOWN	STD STR STA .S/E .SO .SSD .ST .STR .SG .SE,se or e .SYM .TAN .TAN .TS .TEMP .TBM .TH .TSHP .TH .TSHP .TR .CT .TO .TP .TY U.UNK
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK THROAT TOWNSHIP TRIPLE TRIPLE BARREL CULVERT TURN OUT TURNING POINT TYPE UNIT UNKNOWN UNPAVED	STD STR STA .S/E .SO .SSD .ST .STR .SG .SE,se or e .SYM .TAN .TAN .TS .TEMP .TBM .TH .TSHP .TH .TSHP .TY .TY .UNK .UNPVD
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK TTROAT TOWNSHIP TRIPLE TRIPLE BARREL CULVERT TURN OUT TURNING POINT TYPE UNIT UNKNOWN UNPAVED VALLEY GUTTER	STD STR STA SS/E SO SSD ST STR SG SE,se or e SRV SYM TAN TS TEMP TBM TSHP TSHP TCT TO TP TY UNK UNPVD VG
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK THROAT TOWNSHIP TRIPLE TRIPLE BARREL CULVERT TURN OUT TURNING POINT TYPE UNIT UNKNOWN UNPAVED VALLEY GUTTER VARIABLE VFRTICAI	STD STR STA .S/E .SO .SSD .STR .SG .SE,se or e .SYM .TAN .TS .TEMP .TBM .TBM .TBM .TBM .TBM .TBM .TCT .TO .TP .TY .UNPVD .VG .VAR .VFRT
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK THROAT TOWNSHIP TRIPLE TRIPLE BARREL CULVERT TURN OUT TURNING POINT TYPE UNIT UNKNOWN UNPAVED VALLEY GUTTER VARIABLE VFRTICAI	STD STR STA .S/E .SO .SSD .STR .SG .SE,se or e .SYM .TAN .TS .TEMP .TBM .TBM .TBM .TBM .TBM .TBM .TCT .TO .TP .TY .UNPVD .VG .VAR .VFRT
STANDARD STRENGTH STATION STATION & ELEVATION. STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK THROAT TOWNSHIP TRIPLE TRIPLE BARREL CULVERT TURN OUT TURNING POINT TYPE UNIT UNKNOWN UNPAVED VALLEY GUTTER VARIABLE VERTICAL CURVE VERTICAL CURVE VERTICAL POINT OF CURVATURE	STD STR STA SS/E SSO SSD STR SG SE,se or e SRV SYM TAN TS TEMP TBM TH TSHP TR TO TP TY UNK UNPVD VG VAR VERT VC
STANDARD STRENGTH STATION STATION & ELEVATION STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK THROAT TOWNSHIP TRIPLE TRIPLE BARREL CULVERT TURN OUT TURN OUT TURNING POINT TYPE UNIT UNKNOWN UNPAVED VALLEY GUTTER VARIABLE VERTICAL POINT OF CURVATURE VERTICAL POINT OF INTERSECTION	STD STR STA SS/E SO SSD STR SG SE,se or e SRV SYM TAN TSHP TBM TSHP TSHP TR CT TO TP TY UNK UNPVD VG VAR VERT VC PVI
STANDARD STRENGTH STATION STATION & ELEVATION. STATION & OFFSET STOPPING SIGHT DISTANCE STREET STRUCTURE SUB-GRADE SUPERELEVATION SURVEY SYMMETRICAL TANGENT TANGENT LENGTH (CURVE DATA) TANGENT TO SPIRAL TEMPORARY TEMPORARY BENCH MARK THROAT TOWNSHIP TRIPLE TRIPLE BARREL CULVERT TURN OUT TURNING POINT TYPE UNIT UNKNOWN UNPAVED VALLEY GUTTER VARIABLE VERTICAL CURVE VERTICAL CURVE VERTICAL POINT OF CURVATURE	STD STR STA SS/E SSD SST SSTR SE,se or e SSYM TAN TSHP TBM TSHP TR TY UNK UNPVD VG VAR VERT VC PVI PVI

#### STRUCTURES

NUMBER OF STORIESFRAME	1,2,3,4
BUILDING	RI DG
BLOCK.	
BRICK	
STUCCO	STU
METAL	
RESIDENCE	
BUSINESS	
WAREHOUSE	.WHSE
CHICKEN HOUSE	
CHURCH	
SCHOOL	
DOUBLE WIDE MOBILE HOME	
MOBILE HOME	MH

#### UTILITIES

ANCHOR WIRE	Δ\٨/
BURIED ELECTRIC	
BURIED ELECTRIC	BE
BURIED FIBER OPTIC	BFO
BURIED TELEPHONE CABLE	RTC
	DTC
BURIED CABLE TELEVISION	BIV
CAST IRON	.CI
CIRCUIT	CKT
DUCTILE IRON	DUC IRON
EASEMENT	.FSMT
FIBER OPTIC	EO
FIRE HYDRANT FORCED MAIN (SANITARY SEWER)	.FH
FORCED MAIN (SANITARY SEWER)	.FM
GAS MAIN`	CM
	ONACT
GAS METER	GMET
GAS VALVE	GV
GUY WIRE	CLIV
	GUI
HIGH PRESSURE	.HP
KILOVOLT AMPS	.KVA
MANHOLE	MH
MERCURY VAPOR LIGHT	- IVII I - N 43 /I
MERCURY VAPOR LIGHT	·MVL
OVERHEAD FIBER OPTIC	.OFO
OVERHEAD TELEPHONE CABLE	OTC
	.010
OVERHEAD ELECTRIC CABLE	.OE
OVERHEAD CABLE TELEVISION	OTV
PAIR	
PEDESTAL POLY-VINYL CHLORIDE PIPE	.PED
POLY-VINYL CHLORIDE PIPE	.PVC
POWER POLE	PP
	00
SANITARY SEWER	55
SERVICE	.SERV
STEEL	STI
STORM DRAIN	CTM
510RW DRAIN	2 I IVI
STORM SEWER	STMS
SWITCH	SW
TELEDHONE	TEI
TELEPHONETELEPHONE MANHOLE	. I CL
TELEPHONE MANHOLE	.TMH
TRANSFORMERTRANSMISSION LINE	TRAN
TDANICMICCION I INE	TDIN
TRANSIMISSION LINE	TOX
TRIAXIAL CABLE (SERVICE) VITRIFIED CLAY PIPE	IRIX
VITRIFIED CLAY PIPF	VCP
WATER MAIN	\\/\/\
	V V IVI
WATER METER	VVIVIE I
WATER VALVE	WV
	= =


#### PROPERTY

DEED BOOK	RP PB MB PG OR
CAPPED (TYPICAL PLASTIC SURVEYORS CAP) ALUMINUM CAPBRASS CAP	. ALUM CAP
IRON PIPECRIMPED	IP CR
REINFORCING STEELCONCRETE MONUMENT	CM
DAMAGED CHISELED X HUB AND TACK	CH"X"
NAIL AND BOTTLE TOPPARKER-KALON (MASONARY NAILS)	N&BT
FENCE POSTRAILROAD IRON	. F-POST
COTTON SPINDLEANGLE IRON	









# le Airport Authority Alabama

# MAA TERMINAL RELOCATION

Mobile A	MAA TE RELOC	Mobile,
REVISIO	ON HISTORY	
	DESCRIPTION OT INFORMATION	DATE
DESIGN		

$\triangle$	DESCRIPTION	DATE
PROJEC	CT INFORMATION	
DESIGN	ED BY:	
JNR		DSG
DRAWN	BY:	
JNR		DRN
REVIEW	/ED BY:	
HZE		CHK
PROJEC	CT MANAGER:	
JNR		DOG
PROJEC	T NUMBER	
11492	11	

PLANS LEGEND SHEET ABBREVIATIONS

ISSUE DATE


SHEET TITLE:

#### **SAFETY NOTES:**


- DURING ALL WORK WITHIN THE AIR OPERATIONS AREA (AOA) THE CONTRACTOR SHALL CONTINUOUSLY MONITOR THE TOWER RADIO FREQUENCY 118.800 MHZ AND GROUND FREQUENCY 121.700 MHZ. IF THE AIR TRAFFIC CONTROL TOWER IS NOT MANNED, THE CONTRACTOR SHALL MONITOR CTAF RADIO FREQUENCY 118.800 MHZ. THE CONTRACTOR IS REQUIRED TO HAVE TWO (2) AVIATION BAND RADIOS ON SITE FOR THIS PURPOSE. NO DIRECT PAY.
- THE CONTRACTOR SHALL COMPLY WITH THE DEPARTMENT OF TRANSPORTATION FEDERAL AVIATION ADMINISTRATION ADVISORY CIRCULAR (AC) 150/5370-2G. THE CONTRACTOR SHALL ADHERE TO ALL SAFETY REGULATIONS OF THE AC AND ITS REFERENCES AND TO ALL OTHER ADVISORY MATERIAL PERTAINING TO OPERATIONAL SAFETY ON AIRPORTS WITH EMPHASIS ON SAFETY DURING CONSTRUCTION.
- ALL VEHICLES USED ON THE AIRFIELD SHALL BE IN COMPLIANCE WITH AC 150/5210-5D PAINTING, MARKING, AND LIGHTING OF VEHICLES USED ON AIRPORTS.
- ALL CONSTRUCTION GATES SHALL BE LOCKED OR GUARDED AT ALL TIMES.
- IF THE CONTRACTOR DAMAGES OR REMOVES A SECTION OF FENCE AROUND THE AOA HE SHALL INSTALL A TEMPORARY FENCE OR POST A GUARD AT THE OPENING. FENCE REPAIR/REPLACEMENT, GUARDS, BARRICADES, ETC. NECESSARY TO MAINTAIN SECURITY IN THE AOA SHALL BE PROVIDED AT NO COST TO THE OWNER.
- IT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR TO DETERMINE THAT EQUIPMENT USED WILL NOT DAMAGE THE HAUL ROUTES. ANY DAMAGE TO THE HAUL ROUTES OR OTHER PAVEMENTS SHALL BE REPAIRED BY THE CONTRACTOR AT NO COST TO THE OWNER. REPAIR METHODS SHALL MEET CURRENT DOT STANDARDS AND BE APPROVED BY THE OWNER.
- ALL DISTURBED OR DAMAGED AREAS OR ITEMS SHALL BE RESTORED TO THEIR ORIGINAL CONDITION BY THE CONTRACTOR AT NO DIRECT COST TO THE OWNER.
- THE CONTRACTOR SHALL CONTINUALLY KEEP ALL PAVED AREAS FREE OF DEBRIS. DIRT. AND MUD.
- AT ALL TIMES THE CONTRACTOR SHALL USE CARE NOT TO ALLOW PAPER, PLASTIC, OR ANY OTHER TRASH TO BE LOOSE ON THE JOB SITE. ALL SUCH MATERIAL SHALL BE CONTROLLED AND DISPOSED OF PROPERLY. ANY LOOSE MATERIAL SHALL BE IMMEDIATELY RETRIEVED.
- 10. THE CONTRACTOR SHALL TAKE NECESSARY PRECAUTIONS AND ACTIONS TO PREVENT AND CONTROL DUST FROM THE CONSTRUCTION SITE. THE CONTRACTOR SHALL CLEAN EXISTING BUILDINGS AND STRUCTURES AS NEEDED OR DIRECTED BY THE ENGINEER. NO DIRECT PAY.
- 11. MATERIAL STORAGE AND STOCKPILE AREAS ARE TO BE KEPT CLEAN AND ORDERLY. CONTRACTOR STAGING AREAS SHOWN ARE APPROXIMATE DIMENSIONS.
- 12. DURING NON-WORKING HOURS, NO EQUIPMENT OR MATERIAL SHALL BE PARKED OR STORED OUTSIDE OF THE DESIGNATED CONTRACTOR STAGING AREAS.
- 13. ISSUANCE OF A NOTICE TO AIRMEN (NOTAM) REQUIRES 48 HOURS PRIOR NOTICE TO THE OWNER. THE CONTRACTOR SHALL COORDINATE HIS WORK SCHEDULE WITH THE ENGINEER, AND REQUEST ISSUANCE OF A NOTAM TO THE OWNER THROUGH THE ENGINEER.
- 14. THE CONTRACTOR SHALL FIELD VERIFY EXISTING CONDITIONS PRIOR TO THE START OF CONSTRUCTION AND REPORT TO THE ENGINEER ANY VARIATIONS FROM THE INFORMATION SHOWN IN THE CONSTRUCTION DOCUMENTS. NO DIRECT PAY.
- 15. THE CONTRACTOR SHALL BE RESPONSIBLE FOR LOCATING ALL UTILITIES PRIOR TO CONSTRUCTION. NO DIRECT PAY.
- 16. FOR AIRPORT SECURITY REQUIREMENTS, SEE DIVISION I SECTION B OF THE SPECIFICATIONS.
- 17. FOR ADDITIONAL SAFETY PLAN ITEMS ON THIS PROJECT, SEE DIVISION III, SECTION 160 OF THE SPECIFICATIONS.
- 18. THE CONTRACTOR SHALL COORDINATE ALL WORK WITH AIRPORT, OWNER, AND THE ENGINEER.
- 19. REFER TO SHEET 2A FOR ADDITIONAL SAFETY REQUIREMENTS.

SEQUENCE OF CONSTRUCTION:				
PHASE	PHASE DESCRIPTION OF WORK			
PHASE 0	OBTAIN NECESSARY PERMITTING AND PROVIDE SHOP DRAWINGS AND SUBMITTALS TO ENGINEER.			
	PERFORM REQUIRED AIRPORT SAFETY / SECURITY TRAINING AND OBTAIN SECURITY BADGES.			
	COORDINATE WITH ENGINEER, AIRPORT, AND OWNER.			
	NOTIFY AIRPORT SPONSOR FOR ISSUANCE OF REQUIRED NOTAMS.			
	INSTALL REQUIRED SAFETY AND TRAFFIC CONTROL DEVICES.			
PHASE 1	INSTALL TEMPORARY FENCING WITHIN AIR OPERATIONS AREA (AOA) AROUND BUILDING 2 TO BE			
	REMOVED AS SHOWN ON SHEET 4.			
	INSTALL TEMPORARY FENCING AND CONSTRUCTION GATE ALONG PERIMETER ROAD AS			
	SHOWN ON SHEET 4.			
	REMOVE EXISTING FENCE ALONG MICHIGAN AVENUE AS SHOWN ON SHEET 4			
	DEMOLISH EXISTING BUILDINGS TO BE REMOVED AS SHOWN ON SHEET 4			
	REMOVE CONCRETE PAVEMENT AS SHOWN ON SHEET 4			
PHASE 2	INSTALL PERMANENT FENCE OFF MICHIGAN AVENUE IN PLACE OF BUILDING 2 AS SHOWN ON SHEET 4.			
FIIAGE 2				
	REMOVE TEMPORARY FENCE WITHIN THE AIR OPERATIONS AREA (AOA) INSTALL PERMANENT VEGETATION.			
	INSTALL PERIVANENT VEGETATION.			
PHASE 3	PERFORM INSPECTION OF REQUIRED WORK WITH THE ENGINEER AND OWNER.			
	CORRECT AND/OR REPAIR DEFICIENCIES, AND CLEAN UP THE SITE.			
	PERFORM FINAL INSPECTION.			
	REMOVE REMAINING BMPs.			
	REMOVE REMAINING SAFETY AND TRAFFIC CONTROL DEVICES.			
	DEMOBILIZE.			
TOTAL				
PROJECT	PROJECT			
TIME				









## uthority **Airport** ATION MAA RELO Mobil Mobil

Alabama


REVISION HISTORY DESCRIPTION DATE PROJECT INFORMATION

DESIGNED BY JNR DSG DRN JNR REVIEWED BY: CHK PROJECT MANAGER: DOG

1149211 SHEET TITLE:

SAFETY NOTES


ISSUE DATE


















Alabama

Authority

ile Airport



	DESCRIPTION	DATE
PROJEC	CT INFORMATION	
DESIGN	ED BY:	
JNR		DSG
DRAWN	BY:	
JNR		DRN
REVIEW	/ED BY:	
HZE		CHK
PROJEC	CT MANAGER:	
JNR		DOG
PROJEC	T NUMBER	
11492	11	

SHEET TITLE: CONSTRUCTION SAFETY PHASING PLAN SHEET

ISSUE DATE

PROJECT NOTES:

- 1 ITEM NO. 665N-000 TEMPORARY COARSE AGGREGATE, ALDOT NUMBER 1 HAS BEEN SET UP FOR PROVIDING OR MAINTAINING ACCESS TO AND FROM EACH STRUCTURE REMOVAL SITE AND SHALL BE USED AS DIRECTED BY THE PROJECT ENGINEER.
- 2 2704 CUBIC YARDS OF ITEM NO 210D-022 BORROW EXCAVATION (LOOSE TRUCKBED MEASUREMENT) (A-2-4(0) OR A-4(0)) HAS BEEN SET UP AS FILL MATERIAL AND SHALL BE USED AS NEEDED AT EACH STRUCTURE REMOVAL SITE AS DIRECTED BY THE PROJECT ENGINEER.
- 3 ALL DISTURBED AREAS SHALL BE PLATED WITH APPROXIMATELY 4 INCHES OF ITEM NO. 650A-000 TOPSOIL PRIOR TO SEEDING AND MULCHING, VEGATION SHALL BE ESTABLISHED TO A PRE-EXISITING CONDITION FOR ALL DISTRIBUTED AREAS AND SHALL BE TO THE SATISFACTION OF THE PROJECT ENGINEER.
- 4 ALL DEBRIS SHALL BE REMOVED BY RAZING OTHERWISE DISPOSING OF THE STRUCTURE/DEBRIS OFF MAA PROPERTY,
  STONES, BRICKS, BROKEN CONCRETE, CONCRETE BLOCKS, AND CONCRETE MASONRY OF ALL TYPES MAY NOT BE USED TO FILL LOW AREAS, EXISTING WELLS, BASEMENTS, AND OTHER DEPRESSIONS.

THE CONTRACTOR SHALL GRADE THE SITES TO PROVIDE POSITIVE DRAINAGE AS A SUBSIDIARY OBLIGATION


- 5 CLEARING AND GRUBBING, IF REQUIRED, SHALL BE A SUBSIDIARY OBLIGATION OF ITEM NO. 205A.
- 6 THE REMOVAL OF STRUCTURES REQUIRED IN THIS PROJECT SHALL INCLUDE ABANDONMENT OF ANY EXISTING SEPTIC TANKS, FILL LINES, AND CONTENTS IN ACCORDANCE WITH ALABAMA DEPARTMENT OF PUBLIC HEALTH REQUIREMENTS. ALL SEPTIC TANKS LOCATED INSIDE OF THE EXISTING AND ACQUIRED RIGHT-OF-WAY SHALL BE REMOVED AND DISPOSED OF OFF MAA PROPERTY.
- 7 OMITTED
- 8 IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO CONTACT THE VARIOUS UTILITY OWNERS AND DETERMINE THE EXACT LOCATION OF ALL EXISTING UTILITIES ON THIS PROJECT WHETHER SHOWN ON THE PLANS OR NOT.
- 9 OMITTED
- 10 OMITTED
- 11 THE CONTRACTOR SHALL FILE ADEM FORM 496 AT LEAST 10 DAYS PRIOR TO THE REMOVAL OF ANY STRUCTURE
- WITH THE APPROPRIATE REGULATORY AUTHORITY AS DESIGNATED BY THE FORM'S INSTRUCTIONS.
- 12 THE PROJECT IS SUBJECT TO ALL INSPECTIONS PROVIDED IN THE CONTRACT DOCUMENTSAND TO INSPECTIONS BY REPRESENTATIVES OF THE MOBILE AIRPORT AUTHORITY, THE FEDERAL AVIATION ADMINISTRATION (FAA), THE CITY OF MOBILE, AND THE ALABAMA DEPARTMENT OF ENVIRONMENTAL MANAGEMENT (ADEM).
- 13 THE CONTRACTOR SHALL COORDINATE ALL CONSTRUCTION ACTIVITIES WITH THE ENGINEER, THE OWNER, AND OTHER CONTRACTORS AND UTILITY COMPANIES AT, OR IN CLOSE PROXIMITY TO THE SITE.
- 14 ALL CONTRACTOR VEHICLES SHALL BE FLAGGED AND/OR LIGHTED IN ACCORDANCE WITH SPECIFICATION SECTION 160, "SAFETY PLAN FOR THE AIR OPERATIONS AREA". ONLY THE ESSENTIAL VEHICLES AND EQUIPMENT PROPERLY MARKED AND ACTIVELY ENGAGED IN THE WORK WILL BE PERMITTED WITHIN THE AIR OPERATIONS AREA. ALL OTHER VEHICLES SHALL BE PARKED AT AREAS PROVIDED BY THE CONTRACTOR AND APPROVED BY THE ENGINEER.
- 15 THE CONTRACTOR SHALL NOTIFY THE ENGINEER ONE-HOUR PRIOR TO THE COMPLETION OF EACH WORKING SHIFT SO THAT THE CONDITION OF THE WORK AREA CAN BE INSPECTED. THE CONTRACTOR SHALL REMAIN ON SITE, WITH AN ADEQUATE LABOR FORCE, UNTIL ALL INSPECTION IS COMPLETED. ANY DEFICIENCIES SHALL BE IMMEDIATELY CORRECTED.

- THE LOCATION OF THE HAUL ROUTE ON THE AIRPORT SITE IS SHOWN ON THE SAFETY PLAN AND IS SUBJECT TO CHANGE. IT SHALL BE THE CONTRACTORS RESPONSIBILITY TO INSPECT THE HAUL ROUTE LEADING TO THE SITE AND DETERMINE THAT HIS EQUIPMENT, MEANS, AND METHODS WILL NOT CAUSE DAMAGE TO THE HAUL ROUTE. IT SHALL BE THE CONTRACTOR'S RESPONSIBILITY TO COORDINATE OFF-SITE ACCESS ROUTES (STATE HIGHWAYS, LOCAL ROADS, OR CITY STREETS) WITH THE APPROPRIATE OWNER HAVING JURISDICTION OVER THE AFFECTED ROUTE. CONTRACTOR PERMISSION TO USE PUBLIC ROADS FOR HAULING AND ACCESS SHALL BE OBTAINED FROM THE APPROPRIATE PUBLIC ENTITIES. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO OBTAIN ALL NECESSARY PERMITS, APPROVALS AND BONDING. THE CONTRACTOR SHALL DETERMIN WHICH NON-AIRPORT ROADS SHALL BE BONDED, AND SHALL BOND SUCH ROADS. ANY DAMAGE CAUSED BY THE CONTRACTOR'S ACTIVITIES TO ANY HAUL ROUTE SHALL BE REPAIRED BY THE CONTRACTOR AT NO COST TO THE OWNER.
- 17 THE CONTRACTOR SHALL COORDINATE WITH THE MOBILE AIRPORT AUTHORITY, THE CITY OF MOBILE, AND OTHER OWNERS HAVING JURISDICTION TO ENSURE THE HAUL ROUTE SELECTED WILL SUPPORT LOADS THE CONRACTOR PLANS TO HAUL. THE CONTRACTOR SHOULD NOT ASSUME ALL ROADS WILL SUPPORT THE LEGAL LIMIT. ANY DAMAGE CAUSED BY THE CONTRACTOR'S EQUIPMENT, MEANS, OR METHODS SHALL BE REPAIRED AT NO COST TO THE OWNER
- 18 THE CONTRACTOR SHALL DEVELOP AND SUBMIT A PLAN FOR OFF SITE HAUL ROUTES TO THE ENGINEER PRIOR TO THE START OF CONSTRUCTION. THE BEFORE AND AFTER CONDITION OF HAUL ROUTES SHALL BE JOINTLY INSPECTED AND PHOTOGRAPHED BY THE CONTRACTOR AND THE ENGINEER. HAUL ROUTES SHALL BE MAINTAINED BY THE CONTRACTOR THROUGHOUT CONSTRUCTION AND RESTORED UPON COMPLETION OF CONSTRUCTION IN ACCORDANCE WITH THE CONTRACT DOCUMENTS AT NO COST TO THE OWNER.
- 19 THE CONTRACTOR SHALL COORDINATE WITH THE RPR AND OWNER TO DETERMINE A SUITABLE LOCATION FOR EQUIPMENT, MATERIAL, AND STORAGE OR STAGING. THE LOCATION OF STORAGE OR STAGING AREAS SHALL BE BASED ON THE SIZE AND WEIGHT OF EQUIPMENT AND THE RISK OF POTENTIAL DAMAGE TO EXISTING INFRASTRUCTURE. THE CONTRACTOR WILL BE RESPONSIBLE FOR INSURING THE STAGING AREA IS CAPABLE OF SUPPORTING ALL PROPOSED EQUIPMENT, MATERIAL, OBJECTS, ETC. ANY DAMAGE TO EXISTING INFRASTRUCTURE SHALL BE REPAIRED, AND/OR REPLACED BY THE CONTRACTOR AT NO COST TO THE OWNER.
- 20 ALL CONTRACTOR VEHICLES AND CONSTRUCTION TRAFFIC SHALL REMAIN WITHIN THE DESIGNATED CONSTRUCTION LIMITS OR HAUL ROUTES UNLESS OTHERWISE AUTHORIZED.
- 21 EROSION CONTROL AND OTHER MISCELLANEOUS CONSTRUCTION REQUIRED TO CONSTRUCT ADDITIONAL HAUL ROUTES OR ACCESS POINTS ON THE AIRPORT WILL BE THE CONTRACTOR'S RESPONSIBILITY, AND SHALL BE APPROVED BY THE ENGINEER PRIOR TO THE COMMENCEMENT OF THE WORK. ALL ROADS TO AIRPORT FACILITIES SHALL REMAIN OPEN AND MAINTAINED AT ALL TIMES. NO DIRECT PAYMENT.
- 22 DATES AND TIMES WILL BE ESTABLISHED AT THE PRE-CONSTRUCTION CONFERENCE FOR WEEKLY PROGRESS MEETINGS TO BE HELD WITH THE CONTRACTOR, ENGINEER, AND AIRPORT OWNER. THE CONTRACTOR'S SUPERINTENDENT AND SAFETY OFFICER SHALL ATTEND EACH MEETING, ADDITIONAL ATTENDEES MAY INCLUDE AIRPORT TENANTS, UTILITY COMPANY REPRESENTATIVES, OR OTHERS.
- 23 OMITTED
- 24 ALL WORK SHALL BE COMPLETED IN SUFFICIENT TIME EACH DAY TO ALLOW FOR ADEQUATE CLEAN UP AND INSPECTION OF WORK AREA.
- 25 THE CONTRACTOR IS RESPONSIBLE FOR THE PROTECTION OF THE AIRPORT PAVEMENT, LIGHTING, AND NAVAIDS DURING CONSTRUCTION. ALL DAMAGE RESULTING FROM THE CONTRACTOR'S ACTIONS SHALL BE REPAIRED IMMEDIATELY AT THE CONTRACTOR'S EXPENSE.
- 26 CONTRACTORS ARE REQUIRED TO CONSIDER THE SERVICES OF MINORITY AND DISADVANTAGED BUSINESSES WHEN COMPETENT FIRMS ARE AVAILABLE. CONTRACTOR CONTRACT REQUIREMENTS FOR MINORITY BUSINESS ENTERPRISES (MBE) AND WOMEN BUSINESS ENTERPRISES (WBE) SHALL BE AS STATED IN SECTION 150 OF THE CONTRACT SPECIFICATIONS.
- 27 ALL GRASS AREAS THAT ARE DISTURBED BY THE CONTRACTOR SHALL BE RESTORED AND GRASSED TO PRE-CONSTRUCTION CONDITION. THERE WILL BE NO DIRECT PAY FOR THIS WORK.









uthority

**Airport** 

O

MAA TERMINAL RELOCATION Mobile, Alabama

	Nobil	WAA ?ELC	Mobil
В	REVISIO	ON HISTORY	
		DESCRIPTION	DATE
	PROJEC	CT INFORMATION	ı

$\triangle$	DESCRIPTION	DATE
PROJEC	CT INFORMATION	
DESIGN	ED BY:	
JNR		DSG
DRAWN	BY:	
JNR		DRN
REVIEW	/ED BY:	
HZE		CHK
PROJEC	CT MANAGER:	
JNR		DOG
PROJEC	T NUMBER	
11492	11	

PROJECT NOTES

ISSUE DATE

SHEET TITLE:

17 August, 2023
SHEET NUMBER

2B

3


- 28 ANY FINES LEVIED AGAINST THE OWNER DUE TO CONTRACTOR'S OPERATIONS AND/OR ACTIVITIES SHALL BE PAID BY THE CONTRACTOR.
- 29 THE CONTRACTOR SHALL BE RESPONSIBLE FOR THE SAFETY, EFFICIENCY, AND ADEQUACY OF HIS OPERATION AND SHALL INITIATE HIS OWN SAFETY PROGRAM. THE CONTRACTOR SHALL COMPLY WITH ALL DEPARTMENT OF LABOR, SAFETY, AND HEALTH REGULATIONS AS SPECIFIED UNDER THE OCCUPATIONAL SAFETY AND HEALTH ACT OF 1970, AS AMENDED, AND THE CONTRACT WORK HOURS AND SAFETY STANDARDS ACT.
- 30 IT WILL BE THE CONTRACTOR'S RESPONSIBILITY TO DETERMINE IF THE REQUIRED CONSTRUCTION CAN BE PERFORMED WITHIN THE AREA PROVIDED AND COMPLY WITH THE REQUIREMENTS OF THE OCCUPATIONAL SAFETY AND HEALTH REGULATION (OSHA) FOR CONSTRUCTION PROJECTS OF THIS TYPE. ANY SAFETY MEASURES OR METHOD OF CONSTRUCTION THAT IS NECESSARY IN THE CONSTRUCTION OF THIS PROJECT TO COMPLY WITH THESE REGULATIONS IS THE CONTRACTOR'S RESPONSIBILITY AND SHALL BE PROVIDED WITH ALL COSTS TO BE INCLUDED IN THE VARIOUS PAY ITEMS OF THE CONTRACT(NO DIRECT PAYMENT).
- 31 OMITTED
- 32 THE CONTRACTOR SHALL NOT USE AIRPORT TERMINAL OR FBO FACILITIES.
- 33 PRODUCT SUBMITTALS AND SHOP DRAWINGS SHALL BE SUBMITTED AT LEAST 7 DAYS PRIOR TO INSTALLATION OF THE PRODUCT.
- 34 OMITTED
- 35 THE CONTRACTOR SHALL FIELD VERIFY ALL UTILITIES AND DRAINAGE STRUCTURES PRIOR TO THE START OF CONSTRUCTION.
- 36 THE CONTRACTOR SHALL BE RESPONSIBLE FOR OBTAINING ALL PERMITS AND COSTS ASSOCIATED WITH REQUIRED PERMITS. A LAND DISTURBANCE BOND IN THE AMOUNT OF \$3,000.00 PER ACRE OF DISTURBED AREA WILL BE REQUIRED BY THE CITY OF MOBILE IN ORDER TO OBTAIN A LAND DISTURBANCE PERMIT FOR THIS PROJECT. NO DIRECT PAY.
- 37 OMITTED
- 38 THESE PLANS HAVE BEEN PREPARED TO CONFORM WITH ALDOT STANDARDS AND SPECIFICATIONS FOR HIGHWAY CONSTRUCTION 2022 EDITION. ALL CONSTRUCTION MATERIALS. CONSTRUCTION REQUIREMENTS. METHOD OF MEASUREMENT, AND BASIS OF PAYMENT SHALL BE IN ACCORDANCE WITH THE SPECIFICATION FOR THE RELEVANT PAY ITEM.
- 39 ALL REQUIRED IMPROVEMENTS, EQUIPMENT, AND WORKMANSHIP SHALL BE COMPLETED IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS.
- 40 OMITTED
- 41 THE CONTRACTOR SHALL BE RESPONSIBLE FOR ANY DAMAGE DONE BY HIS EQUIPMENT TO EXISTING UTILITIES, STORM DRAIN, DRAINAGE STRUCTURES, PIPES AND HEADWALLS OR OTHER EXISTING SITE FEATURES TO REMAIN, INCLUDING OWNER MATERIAL STORED ON-SITE. ALL DAMAGED ITEMS SHALL BE REPLACED IN LIKE KIND AT NO ADDITIONAL COST TO THE OWNER.
- 42 ALL PROPERTY LINE MARKERS (IRON PINS, CONCRETE MONUMENTS, ETC.) DESTROYED DURING CONSTRUCTION SHALL BE REPLACED IN KIND BY THE CONTRACTOR AT NO ADDITIONAL COST TO THE OWNER. THE CONTRACTOR SHALL EMPLOY A LAND SURVEYOR REGISTERED IN THE STATE OF ALABAMA TO RESET PROPERTY MARKERS.
- 43 ALL EXCAVATION, SHORING AND BRACING SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- 44 TRAFFIC REGULATIONS AND CONTROL ON AND ADJACENT TO THE PROJECT AREA SHALL BE IN ACCORDANCE WITH THE MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES (MUTCD), LATEST EDITION.

- 45 DURING CONSTRUCTION OPERATIONS, THE CONTRACTOR SHALL TAKE MEASURE TO PREVENT SOIL SEDIMENT AND TURBIDITY FROMWASHING INTO ALL CREEKS. BRANCHES, STREAMS, RIVERS, PRIVATE OR PUBLIC PROPERTY.
- 46 OMITTED
- 47 OMITTED
- 48 CONTRACTOR SHALL ABIDE BY THE CITY OF MOBILE LITTER ORDINANCE.
- 49 OMITTED
- 50 OMITTED
- 51 OMITTED
- 52 OMITTED
- 53 OMITTED
- 54 OMITTED
- 55 CONTRACTOR SHALL COORDINATE WITH APPROPRIATE UTILITY COMPANIES PRIOR TO CONSTRUCTION, ADJUSTMENT OR RELOCATION OF EXISTING UTILITIES.
- 56 ALL MEASUREMENTS SHOWN IN FEET UNLESS NOTED OTHERWISE.
  - LAND DISTURBANCE NOTES
- CONTRACTOR SHALL CONTACT THE CITY ENGINEERING DEPARTMENT VIA EMAIL AT land.disturbance@cityofmobile.org AT LEAST24 HOURS PRIOR TO BEGINNING ANY WORK ON THIS SITE TO SCHEDULE AN INITIAL ON-SITE BMP INSPECTION WITH THE APPROPRIATE CITY ENGINEERING INSPECTOR. FAILURE TO CONTACT THE CITY ENGINEERING DEPARTMENT PRIOR TO BEGINNING WORK IS A VIOLATION OF THE STORM WATER MANAGEMENT AND FLOOD CONTROL ORDINANCE AND MAY INVOKEENFORCEMENT ACTION IN THE FORM OF A MUNICIPAL OFFENSE TICKET
- 2 THE LDP EXPIRES UPON THE COMPLETION OF THE WORK OR NOT LATER THAN ONE (1) YEAR FROM THE DATE
- 3 OMITTED
- 4 THE CONTRACTOR SHALL SIZE, INSTALL, AND MAINTAIN ADEQUATE CONTROLS FOR THE SITE. REFER TO THE ALABAMA HANDBOOK FOR EROSION CONTROL, SEDIMENT CONTROL, AND STORMWATER MANAGEMENT ON CONSTRUCTION SITES AND URBAN AREAS, LATEST EDITION.
- 5 THE CONTRACTOR IS RESPONSIBLE FOR DAILY INSPECTION AND CONTINUED MAINTENANCE OF EROSION CONTROL ELEMENTS.
- 6 DISTURBED AREA(S) MAY NOT REMAIN DENUDED LONGER THAN 10 DAYS PER ADEM MS-4 PERMIT CONDITIONS.
- 7 CONTRACTOR WILL BE RESPONSIBLE FOR OBTAINING LAND DISTURBANCE/BUILDING PERMIT FROM THE CITY OF MOBILE AND THE COST ASSOCIATED WITH SECURING PERMIT AND ANY BONDS NEEDED FOR PERMIT









### uthority **Airport** O 0 lobil A IAA EL

Alabama

lido

TION

$\geq$	$\leq \alpha$	<b>\(\)</b>
REVISION	ON HISTORY	
$\triangle$	DESCRIPTION	DATE
PROJE	CT INFORMATION	_


	DECOMM HON	D/\\\
PROJEC	T INFORMATION	
DESIGN	ED BY:	
JNR		DSG
DRAWN	BY:	
JNR		DRN
REVIEW	ED BY:	
HZE		CHK
PROJEC	T MANAGER:	
JNR		DOG
PROJEC	T NUMBER	
11492	11	_

SHEET TITLE:

ISSUE DATE 17 August, 2023

SHEET NUMBER


**PROJECT NOTES** 











# Mobil

REVISION	ON HISTORY			
Δ	DESCRIPTION	DATE		
PROJECT INFORMATION				

Δ	DESCRIPTION	DATE
PROJEC	CT INFORMATION	
DESIGN	ED BY:	
JNR		DSG
DRAWN	BY:	
JNR		DRN
REVIEW	/ED BY:	
HZE		CHK
PROJEC	CT MANAGER:	
JNR		DOG
PROJEC	T NUMBER	


PROJECT DETAILS

NOTE: WHEN BARBED WIRE AND ARMS ARE NOT REQUIRED POSTS SHALL BE NOTE: FABRIC SHALL BE FASTENED TO LINE POST WITH PROPER PROVIDED WITH STANDARD BARBED WIRE ARM BASES SO DESIGNED TIES SPACED APPROXIMATELY 12" APART. FABRIC SHALL BE THAT BARBED WIRE ARMS AND BARBED WIRE MAY BE ADDED AT A ATTACHED TO TOP RAIL WITH TIES SPACED APPROXIMATELY LATER DATE IF DESIRED. (EITHER VERTICAL OR FACING EITHER WAY AT 45° ANGLE) REQUIRING A MINIMUM AMOUNT OF ADDITIONAL WORK, (MALLEABLE IRON GALVANIZED ASTM-A123). 10'-0" MAX. 10'-0" MAX. NOTE: WELDED JOINTS WILL BE ALLOWED PROVIDED WELD IS COVERED WITH A HEATED RE-NOTE: WALK GATES TO BE PLACED - 2" MESH CHAIN-LINK TYPE WEAVE FABRIC MADE OF SPECIAL GALVANIZING ALLOY. AT LOCATIONS SHOWN ON DRAWN WIRE, NO. 9 GAUGE OR HEAVIER GALVANIZED BY THE PLANS. HOT DIP PROCESS (ASTM-A-392) 1.625" O.D. (NOM. ĎÍA.) @< CORNER POSTS 2.375" O.D. (NOM. GATE POSTS 2.375" O.D. (NOM. DIA.) GALV. PIPE DIA.) GALV. PIPE @ 3.65# PER 2.27# PER LIN. FT. GALV. ASTM-A123 TUBING 3.65# PER LIN. FT. FOR 2.875" TO 6' TOP RAIL SHALL BE OF 1.625" O.D. (NOM. DIA.) LIN. FT. (3' TO 6' FENCE) OR  $\stackrel{>}{\sim}$  FENCES 2.875" O.D. (MIN.) GATE POSTS WEIGH-GALV. PIPE & WEIGHT 2.27# PER LIN. FOOT. CORNER POSTS 2.875" O.D. (NOM.  $\stackrel{\checkmark}{\searrow}$  ING NOT LESS THAN 5.79 $\overset{\'}{=}$  PER LIN. FT. FOR RAIL FITTINGS AND FENCE. CONNECTIONS SHALL × 7' TO 12' FENCES. (ASTM-A123) DIA.) GALV. PIPE @ 5.79# PER BE AS DIRECTED BY THE SUPPLYING MANUFACT-BRACES: MATERIAL SAME AS TOP RAIL SPACED LIN. FT. (7' TO 12' FENCE) URER, BUT SHALL INCLUDE ACCEPTABLE EXPAN-MIDWAY BETWEEN TOP RAIL AND GROUND, (ASTM-A123) -FASTENED SECURELY TO POSTS BY SION JOINTS. (ASTM-A123) STEEL CONNECTIONS. (GALV. ASTM-A123) LINE POSTS SHALL BE SPACED NOT TO EXCEED (10) TEN FT. AND SHALL BE OF 1.90" O.D. (NOM. DIA.) GALV. PIPE @ 2.72# PER LIN. FT. FOR 5' TO 6' FENCE WHERE THE ITEM IN THE PROPOSAL FASTENED SECURELY TO POSTS BY  $\stackrel{ o}{
ightarrow}$  FABRIC TO MATCH FENCE REQUIRED REQUIRES FENCE FROM 7' TO 12' IN HEIGHT, THE STEEL CONNECTIONS. (GALV. ASTM-A123) APPROPRIATE BRACES & FITTINGS. LINE POSTS SHALL BE 2.375" (MIN.) O.D. @ NOT LESS THAN 3.65# PER LIN. FT. (ASTM-A123) TRUSS ROD OR BRACE 3/8" RODS & TRUSS ROD OR BRACE 3/8" Ø ROD & TURNBUCKLE TURNBUCKLES ? 3/8" Ø ROD & TURNBUCKLE (GALV. ASTM-A123) ---(GALV. ASTM-A123) NOTE: PREPARE GROUND SURFACE TO CONFORM TO REQUIRED NOTE: ONE PULL ASSEMBLY AS SHOWN ABOVE WILL BE PROFILE OF TOP OF FENCE, AND REMOVE STUMPS TO REQUIRED FOR EACH 500 FT. OF FENCE, AND AT BELOW GROUND SURFACE BEFORE DIGGING POST HOLES. ALL SHARP BREAKS IN TERRAIN. GATE FRAMES TO BE CONuthority I I NOTE: THE CONTRACTOR SHALL PROVIDE A SUPPORT UNDER NOTE: WHERE BREAKS IN PROFILE OF FENCE TOP ARE STRUCTED OF 1.625" O.D. (NOM. CORNER POST, LINE POST, BRACE POST AND END POST TO NECESSARY IN ROUGH TERRAIN, THEY SHALL BE DIA.) GALV. PIPE, COMPLETE ASSURE THE TWO INCH (2") CLEARANCE BETWEEN POST AND MADE IN THE LEAST NUMBER OF INTERVALS WITH HINGES, CATCHES, BRACES I I BOTTOM OF CONCRETE AS SHOWN. PRACTICAL. BREAKS SHALL BE SPREAD OVER AND OTHER NECESSARY FIT-VERTICAL CURVES OF SUFFICIENT LENGTHS TO TINGS, INCLUDING LOCK, 2 KEYS !!! AND ONE (1) MASTER KEY FOR INSURE A PLEASING APPEARANCE. EACH GATE. (GALV. ASTM-A123) **GATE POST** LINE POST **GATE POST** LINE POST END & CORNER POST **Airport** SAWED NOTCH 3/16" - 1/4" WIDE ROD TO BE FASTENED TO STEEL TIE WIRES 10 GA. MIN. — EXTRA LENGTH POSTS SHALL BE USED 1/8" DEEP T EACH BARBED FABRIC. STEEL ROD (1002" ) AT DRAINS IF NEEDED AS DIRECTED WIRE STRAND -14'-0" OR 20'-0" AS NOTED ON PLANS **GENERAL NOTES:** NOTE: DRIVE GATES TO BE PLACED AT LOCATIONS SHOWN ON 1. SETTING FENCE - ALL CONSTRUCTION METHODS AND EQUIPMENT EMPLOYED IN THE SETTING OF FENCE SHALL BE IN ACCORDANCE WITH REQUIREMENTS OF THE SPECIFICATIONS OF THE MANUFACTURER OF THE FENCE MATERIAL Mobil BEING USED AND SUCH THAT THE RESULTING STRUCTURE WILL PROVIDE THE EXPECTED SERVICE, AND BE DURABLE AND COMPLETE IN EVERY DETAIL. NOTE: WELDED JOINTS WILL BE ALLOWED PROVIDED NOTCH 1/8" DEEP WELD IS COVERED WITH A HEATED RE-2. CONCRETE SHALL MEET THE REQUIREMENTS OF SPECIFICATION F-162. GATE POSTS 4" O.D. (NOM. DIA.) IN ROD — GALVANIZING ALLOY. @ 9.10# PER LIN. FT. -3. FOR DETAIL OF FENCE IN DIP SECTIONS, SEE DETAIL THIS SHEET. **ELEVATION** SECTION 4. "H" OR SECTIONS FOR STEEL POSTS OF THE FOLLOWING SIZES AND WEIGHTS ARE ACCEPTABLE FOR USE IN LIEU OF POSTS SHOWN ON THIS SEE DETAIL "D" — DETAIL "E" BARBED WIRE SPACED 2" LINE POST - 1.875x1.625x.113 "H" SECTION @ 2.70# PER LIN. FT. FOR FENCE MIN. OR AS DIRECTED BY EXISTING FENCE PROPOSED FENCE \_ 3' TO 5' IN HEIGHT. THE ENGINEER TO FIT LINE POST - 2.25x1.95x.143 "H" SECTION @ 4.1# PER LIN. FT. FOR FENCE DRAINAGE CONDITIONS 7' TO 12' IN HEIGHT. NOTE: ALTERNATE SCHEMES FOR 6 -1/2" MAX. TOP & MIDDLE RAIL - 1.5x1.3125X.125 "H" SECTION @ 2.27# PER LIN. FT. SECURING WIRE ACROSS SEE DETAIL "E" 6 -1/2" MAX. CORNER POSTS - 2"x2" TUBING @ 3.85# PER LIN. FT. FOR FENCE 3' TO DRAINS MAY BE SUBMITTED 6' IN HEIGHT. FOR APPROVAL. CORNER POSTS - 2.6"x2.5" TUBING @ 5.70# PER LIN. FT. FOR FENCE 7' TO 12' IN HEIGHT. FENCE ARRANGEMENT AT DIP SECTIONS GATE POSTS (DRIVE GATES) - 3"x3" ☐ TUBING @ 9.10# PER LIN. FT. NOT TO SCALE GATE POSTS (WALK GATES) - 2.5"x2.5" ☐ TUBING @ 5.70# PER LIN. FT. 5. ALL SECTIONS MENTIONED ABOVE SHALL BE GALVANIZED (ASTM-A123). 6. OUTSIDE DIMENSIONS SHOWN ABOVE FOR TUBULAR AND "H" SECTIONS ARE STANDARD BAND -— 1/4" MIN. 3/8" MAX. STEEL PLATE (HEATED RE-GALVANIZING ALLOY) 7. CHAIN-LINK FENCE FABRIC SHALL BE KNUCKLE TOP AND KNUCKLE BOTTOM. — 5/16" BOLT O.D. (NOM. DIA.) OF POST NOTE: AN APPROVED EQUAL METHOD DIMENSIONS TO PLUNGER BAR OR BOLT OF CONNECTION MAY BE USED TRUSS ROD OR BRACE BE THE SAME AS THE ACCORDING TO MANU-3/8" Ø ROD & TURNBUCKLE IN LIEU OF CONNECTION DETAIL 11 END OR CORNER POST FACTURERES STANDARD (GALV. ASTM-A123) SHOWN ABOVE. DETAIL. 1/4" HOLES CONNECTION TO EXISTING FENCE 1149211 SHEET TITLE: DETAIL "D" NOTE: GATE FRAME TO BE CONSTRUCTED OF 1.90" O.D. (NOM. DIA.) NOT TO SCALE GALV. PIPE @ 2.72# PER LIN. FT. COMPLETE WITH HINGES, CATCHES, BRACES AND OTHER NECESSARY FITTINGS, INCLUDING LOCK, TWO (2) KEYS, AND ONE (1) MASTER KEY FOR EACH GATE. (GALV. ASTM-A123) LEAF GATES SHEET NUMBER









# Mobil

REVISIO	ON HISTORY				
	DESCRIPTION	DATE			
PROJECT INFORMATION					
DESIGNED BY:					

PROJECT INFORMATION	
DESIGNED BY:	
JNR	DSG
DRAWN BY:	
JNR	DRN
REVIEWED BY:	
HZE	CHK
PROJECT MANAGER:	
JNR	DOG
PROJECT NUMBER	

PROJECT DETAILS

ISSUE DATE


17 August, 2023

PAY AS YOU GO QUANTITY	NON-PAY AS YOU GO QUANTITY	TOTAL QUANTITY	ITEM NO.	UNIT	DESCRIPTION	PROJECT NOTES
,					ALDOT PAY ITEMS	
	1	1	205A001	EACH	REMOVAL OF STRUCTURES, STRUCTURE NO.1	
	1	1	205A002	EACH	REMOVAL OF STRUCTURES, STRUCTURE NO.2	
	1	1	205A003	EACH	REMOVAL OF STRUCTURES, STRUCTURE NO.3	
1		1	205A004	EACH	REMOVAL OF STRUCTURES, STRUCTURE NO.4	
1		1	205A005	EACH	REMOVAL OF STRUCTURES, STRUCTURE NO.5	
1		1	205A006	EACH	REMOVAL OF STRUCTURES, STRUCTURE NO.6	
	1	1	205A007	EACH	REMOVAL OF STRUCTURES, STRUCTURE NO.7	
704	154	858	206C001	SQUARE YARD	REMOVING CONCRETE PAVEMENT	
1080	1624	2704	210D022	CUBIC YARD	BORROW EXCAVATION (LOOSE TRUCKBED MEASUREMENT)(A-2-4(0) OR A- 4(0)	
1		1	600A000	LUMP SUM	MOBILIZATION	
180	271	451	650B000	CUBIC YARD	TOPSOIL FROM STOCKPILES	
1	1	2	652A100	ACRE	SEEDING	
1	1	2	656A010	ACRE	MULCHING	
25	25	50	665F000	EACH	HAY BALES	
25	25	50	665G000	EACH	SAND BAGS	
1756	1450	3206	665J002	LINEAR FOOT	SILT FENCE	
10		10	665N000	TON	TEMPORARY COARSE AGGREGATE, ALDOT NUMBER 1	
1756	1450	3206	6650001	LINEAR FOOT	SILT FENCE REMOVAL	
404		404	740B000	SQUARE FOOT	CONSTRUCTION SIGNS	
25		25	740E000	EACH	CONES (36 INCHES HIGH)	
10		10	740F002	EACH	BARRICADES, TYPE III	
4		4	7401002	EACH	WARNING LIGHTS, TYPE B	
25		25	740M001	EACH	BALLAST FOR CONE	
					FAA PAY ITEMS	
	115	115	F-162-5.2	LINEAR FOOT	REQUIRED CHAIN-LINK FENCE, 7-FT HIGH, WITH 3-STRAND BARBED WIRE	
1		1	F-162-5.3	EACH	20-FT LEAF GATE	
261	252	513	F-162-5.4	LINEAR FOOT	TEMPORARY CHAIN-LINK FENCE (6-FT)	
793	123	916	F-162-5.5	LINEAR FOOT	FENCE REMOVAL	
	252	252	F-162-5.6	LINEAR FOOT	TEMPORARY FENCE REMOVAL	









08/18/2023

Mobile Airport Authority MAA TERMINAL RELOCATION Mobile, Alabama

REVISIO	ON HISTORY	
Δ	DESCRIPTION	DATE
PROJEC	CT INFORMATION	
DESIGN	IED BY:	
JNR		DSG
DRAWN	BY:	
JINR		DRN

	DESCRIPTION	DATE
PROJEC	CT INFORMATION	
DESIGN	ED BY:	
JNR		DSG
DRAWN	BY:	
JNR		DRN
REVIEW	/ED BY:	
HZE		CHK
PROJEC	CT MANAGER:	
JNR		DOG
PROJEC	T NUMBER	
11492°	11	
		•

SHEET TITLE:

SUMMARY OF QUANTITIES

ISSUE DATE

REQUIRED STRUCTURE REMOVAL (205A)					
STRUCTURE NUMBER	LOCA	TION	DESCRIPTION	FUNDED BY PAY AS YOU	
1	NORTHING:	233,203.06	1STORY BUILDING	NO	
I	EASTING:	1,786,542.04	1310KT BULLDING	NO	
2	NORTHING:	233,046.72	1STORY BUILDING	NO	
2	EASTING:	1,786,530.17	1310K1 BUILDING	INO	
3	NORTHING:	232,908.32	1STORY BUILDING	NO	
3	EASTING:	1,785,809.13	1310K1 BUILDING		
4	NORTHING:	233,079.17	1STORY BUILDING	YES	
4	EASTING:	1,785,723.24	1310KT BUILDING	1 5	
5	NORTHING:	233,028.19	1STORY BUILDING	YES	
5	EASTING:	1,785,599.13	1310K1 BUILDING	TES	
6	NORTHING:	233,121.57	1STORY BUILDING	NO	
0	EASTING:	1,785,112.04	1310K1 BUILDING	NO	
7	NORTHING:	232,434.51	1STORY BUILDING	NO	
/	EASTING:	1,786,566.12	1310K1 DUILDING	NO	

FENCE REMOVAL (F-162-5.5)						
FENCE NO.	FR	ОМ	ТО		LENGTH	PAY AS
FEINGE ING.	NORTHING	EASTING	NORTHING	EASTING	(LIN FT)	YOU GO FUNDED
FENCE #1	233,003.40	1,785,394.83	233,251.63	1,785,387.27	248	YES
FENCE #2	232,943.35	1,785,755.91	233,393.23	1,785,731.67	470	YES
FENCE #3	232,943.56	1,785,773.95	232,943.94	1,785,773.95	9	YES
FENCE #4	232,871.57	1,785,784.59	232,805.71	1,785,789.05	66	YES
FENCE #5	233,057.37	1,786,432.69	233,143.82	1,786,486.92	123	NO
	T	OTAL			916	


TEMPORARY FENCE REMOVAL (F-162-5.6)						
DASELINE	FR	ОМ	ТО		LENGTH	PAY AS
BASELINE	NORTHING	EASTING	NORTHING	EASTING	(LIN FT)	YOU GO FUNDED
MICHIGAN AVE	233,143.82	1,786,486.92	233,105.50	1,786,574.96	252	NO
TOTAL					252	

REQUIRED REMOVING CONCRETE PAVEMENT (206C-001)						
NORTHING	EASTING	AREA (SQ	PAY AS YOU GO FUNDED			
233,175.14	1,785,122.19	75	YES			
233,167.50	1,785,251.58	48	YES			
233,086.87	1,785,096.68	64	YES			
233,084.41	1,785,254.14	48	YES			
233,046.84	1,785,454.75	42	YES			
233,047.93	1,785,479.79	95	YES			
233,045.24	1,785,530.86	250	YES			
233,019.56	1,785,664.69	63	YES			
233,082.06	1,785,714.33	19	YES			
233,236.90	1,786,512.90	144	NO			
233,275.63	1,786,572.83	10	NO			
		858				









Mobile Airport Authority
MAA TERMINAL
RELOCATION
Mobile, Alabama

~	<b>S C</b>	2
REVISIO	ON HISTORY	
<u> </u>		
	DESCRIPTION	DATE
PROJEC	CT INFORMATION	

Δ	DESCRIPTION	DATE			
PROJEC	CT INFORMATION				
DESIGN	ED BY:				
JNR		DSG			
DRAWN	BY:				
JNR		DRN			
REVIEW	/ED BY:				
HZE		CHK			
PROJEC					
JNR	JNR				
DRO IEC	T NI IMBER				

PROJECT NUMBER 1149211

SHEET TITLE:

SUMMARY OF QUANTITIES

ISSUE DATE

20	20-FT LEAF GATE (F-162-5.3)						
BASELINE	LOCATION		FACIL	PAY AS			
BASELINE	NORTHING	EASTING	EACH	YOU GO FUNDED			
PERIMETER RD	233,022.15	1,785,028.54	1	YES			
	TOTAL						

REQUIRED EROSION CONTROL SUMMARY (PAY AS YOU GO FUNDED)					
ITEM NUMBER	DESCRIPTION	UNIT	QUANTITY		
665F-000	HAY BALES	EACH	25		
665G-000	SAND BAGS	EACH	25		
665J-002	SILT FENCE	LINFT	1756		
6650-001	SILT FENCE REMOVAL	LINFT	1756		

REQUIRED CHAIN-LINK FENCE, 7-FT HIGH, WITH 3-STRAND BARBED WIRE (F-162-5.2)						
DACELINE	FR	ОМ	ТО		LENGT PAY	
BASELINE	NORTHING	EASTING	NORTHING	EASTING	(LIN FT)	YOU GO FUNDED
MICHIGAN AVE	233,038.95	1,786,494.40	233,078.87	1,786,566.35	115	NO
TOTAL					115	

REQUIRED EROSION CONTROL SUMMARY (NON-PAY AS YOU GO FUNDED)					
ITEM NUMBER	DESCRIPTION	UNIT	QUANTITY		
665F-000	HAY BALES	EACH	25		
665G-000	SAND BAGS	EACH	25		
665J-002	SILT FENCE	LIN FT	1450		
6650-001	SILT FENCE REMOVAL	LIN FT	1450		

SEEDING QUANTITIES SUMMARY (PAY AS YOU GO FUNDED)

UNIT

AC AC

AC

QUANTITY

DESCRIPTION

SEEDING

MULCHING

SEEDING

MULCHING

TEMPORARY CHAIN-LINK FENCE (6-FT) (F-162-5.4)						
DACELINE	FR	ОМ	ТО		LENGT	PAY AS
BASELINE	NORTHING	EASTING	NORTHING	EASTING	(LIN FT)	YOU GO FUNDED
MICHIGAN AVE	233,143.82	1,786,486.92	233,105.50	1,786,574.96	252	NO
PERIMETER RD	232995.704	1785062.736	233242.791	1785028.541	261	YES
TOTAL					513	


SEEDING	QUANTITIES SUMMARY (NON-PAY A	AS YOU GO FL	JNDED)
ITEM	DESCRIPTION	UNIT	QUANTITY

ESTIMATED QUANTITIES						
ITEM NUMBER	DESCRIPTION	UNIT	QUANTITY	STD OR SPECIAL DWG NO		
740B-000	CONSTRUCTION SIGNS	SQ FT	404			
740E-000	CONES (36 INCHES HIGH)	EACH	25	TCD-100		
740F-002	BARRICADES, TYPE III	EACH	10	B-107-2		
7401-002	WARNING LIGHTS, TYPE B	EACH	4	TCD-100		
740M-001	BALLAST FOR CONE	EACH	25			









## bile Airport Authority Alabama IAA TERMINAL ELOCATION Iobile, Alabama

Mc	Z Z	M
REVISIO	N HISTORY	
$\wedge$	DESCRIPTION	DATE
PROJEC	T INFORMATION	

$\triangle$	DESCRIPTION	DATE
PROJEC	CT INFORMATION	
DESIGN	ED BY:	
JNR		DSG
DRAWN	BY:	
JNR		DRN
REVIEW	/ED BY:	
HZE		CHK
PROJEC	CT MANAGER:	
JNR		DOG
PROJEC	T NUMBER	
11492	11	

1149211 SHEET TITLE:

SUMMARY OF QUANTITIES

ISSUE DATE

17 August, 2023 SHEET NUMBER

656A-010

ITEM

652A-100 656A-010

652A-100

STRUCTURE REMOVALS

NORTHING: 233,203.06 EASTING: 1,786,542.04

STR. 2 NORTHING: 233,046.72 EASTING: 1,786,530.17

NORTHING: 232,908.32 EASTING: 1,785,809.13 STR. 4

NORTHING: 233,079.17 EASTING: 1,785,723.24 NORTHING: 233,028.19 EASTING: 1,785,599.13

NORTHING: 233,121.57 EASTING: 1,785,112.04 STR.7

NORTHING: 232,434.51 EASTING: 1,786,566.12

CONSTRUCTION CONTROL POINTS POINT | NORTHING | EASTING | ELEVATION | DESCRIPTION | CP #1 232511.1658 1786204.0873 18.94 

 CP #2
 233528.2630
 1785875.0323
 19.96

 CP #3
 233349.4057
 1786479.5421
 21.89

CRS = CAPPED REBAR SET

REQ'D TEMPORARY

2906 SQ FT

REQ'D 20-FT LEAF GATE

#### GEOMETRIC DATA NOTES:

THE CONTRACTOR SHALL VERIFY EXISTING UTILITIES AND CONSTRUCTION CONTROL POINTS PRIOR TO THE START OF CONSTRUCTION. THE CONTRACTOR SHALL TAKE CARE NOT TO DAMAGE EXISTING UTILITIES.

– EX FENCE #1 TO BE REMOVED

APPROX. 5500 SQ FT - APPROX. 688 SQ FT

- 2. THE CONTRACTOR SHALL BE REPONSIBLE FOR ALL LAYOUT AND CONTROL.
- HORIZONTAL DATUM BASED ON ALABAMA WEST STATE PLANE COORDINATE
- 4. VERTICAL DATUM BASED ON NAD83.

Airport, **O** REVISION HISTORY

08/18/2023 **Authority** 

VOLKERT JESCO, Inc.
Construction **Mobile Airport Authority** 

**100% SUBMITTAL** No. 51304 PROFESSIONAL

Alabama

TERMINA **OCATION** 

△ DESCRIPTION PROJECT INFORMATION DESIGNED BY: DRAWN BY: DRN REVIEWED BY: CHK PROJECT MANAGER: DOG 1149211

DEMOLITION PLAN SHEET

ISSUE DATE

SHEET TITLE:

17 August, 2023 SHEET NUMBER

- EX FENCE #2 TO BE REMOVED

- EX FENCE #3 TO BE REMOVED

APPROX

3575 SQ FT\_

- EX FENCE #4 TO BE REMOVED

CP #1-


EX FENCE #5 TO BE REMOVED -


APPROX-4966 SQ FT

- REQ'D TEMPORARY FENCE

1767 SQ FT

- REQ'D 7-FT FENCE





Mobile Airport Authority


Alabama MAA TERMINAL RELOCATION *l*e, REVISION HISTORY

△ DESCRIPTION PROJECT INFORMATION DESIGNED BY: DSG DRAWN BY: DRN REVIEWED BY: CHK PROJECT MANAGER: DOG

PROJECT NUMBER 1149211 SHEET TITLE:

ULTIMATE PROJECT LAYOUT SHEET

ISSUE DATE



100% SUBMITTAL No. 51304 08/18/2023


Mobile Airport Authority

Mobile Airport Au	MAA TERMINAL RELOCATION	Mobile, Alabama
REVISIO	ON HISTORY	
	DESCRIPTION	DATE
PROJE	T INFORMATION	DATE
DEOLG	155.5%	

Δ	DESCRIPTION	DATE
PROJEC	CT INFORMATION	
DESIGN	IED BY:	
JNR	DSG	
DRAWN	BY:	
JNR		DRN
REVIEW	/ED BY:	
HZE		CHK
PROJEC	CT MANAGER:	
JNR		DOG
PROJEC	CT NUMBER	
4 4 400	4.4	

UTILITY SHEET

ISSUE DATE

















Alabama MAA TERMINAL RELOCATION **/e**, Mobil REVISION HISTORY

△ DESCRIPTION DATE PROJECT INFORMATION DESIGNED BY: DSG DRAWN BY: DRN REVIEWED BY: CHK PROJECT MANAGER: DOG

SHEET TITLE:

TRAFFIC CONTROL PLAN


SHEET NUMBER

(FOR USE WHERE EXCAVATION HAS BEEN DONE, BUT WIDENING IS NOT COMPLETED BY NIGHTFALL OR WHERE PAVEMENT DROP OFF OF RESURFACING PROJECTS IS 3" OR MORE AT NIGHTFALL)

#### TYPICAL FOR DROP-OFF AT EDGE OF PAVEMENT

THE CONTRACTOR IS TO CONSTRUCT A WEDGE OF UNCLASSIFIED EXCAVATION OR CRUSHED AGGREGATE BASE. THE COST OF PLACING AND REMOVAL SHALL BE A SUBSIDIARY OBLIGATION OF THE ADJACENT LAYER.


CHANNELIZING DRUMS SHALL BE PLACED AT 50 FT INTERVALS.




#### NOTES:

- SEE ALDOT'S GENERAL TRAFFIC CONTROL PLAN NOTE NO. 702.
- 2. DRUMS TO BE AS FAR AS PRACTICAL FROM EDGE OF PAVEMENT, MINIMUM DESIRABLE DISTANCE IS 15 FEET FOR FREEWAY TYPE FACILITIES AND 10 FEET FOR OTHER FACILITIES. FOR UNUSUAL CONDITIONS, SUCH AS SPECIAL EQUIPMENT OR LIMITED AVAILABLE SPACE, DIMENSIONS LESS THAN DESIRABLE SHALL BE AS DIRECTED BY THE ENGINEER.
- ALL DEVICES TO BE FURNISHED BY THE CONTRACTOR WITHOUT COST TO THE ALDOT.

DELINEATING DETAIL FOR EQUIPMENT PARKING OR STORING AREA





#### DETAILS FOR TYPICAL PLACEMENT OF TYPE III BARRICADES INSIDE OF CLEAR ZONE

#### DETAILS FOR TYPICAL PLACEMENT OF TYPE

#### III BARRICADES OUTSIDE OF CLEAR ZONE

#### **NOTES**

- SLOPE OF STRIPES ON BARRICADES SHALL BE IN ACCORDANCE WITH SECTION 6F.68 OF THE MUTCD AND DRAWING B-107-2.
- IF SIGNS ARE REQUIRED TO BE USED IN CONJUNCTION WITH TYPE III BARRICADES TO BE PLACED INSIDE THE CLEAR ZONE, THEY SHALL BE POST MOUNTED TO THE SIDE OF THE BARRICADES AS SHOWN.
- IF ROAD CLOSED OR DETOUR SIGNS ARE REQUIRED TO BE USED WITH TYPE III BARRICADES TO BE PLACED OUTSIDE THE CLEAR ZONE, THEY SHALL BE PLACED ON THE TOP OF THE BARRICADES NEAREST THE DETOUR.

#### --SPECIFICATIONS--

#### CURRENT ALABAMA DEPARTMENT OF TRANSPORTATION

THIS DRAWING REPRESENTS DESIGNS PREPARED FOR USE BY THE ALABAMA DEPARTMENT OF TRANSPORTATION AND IS NOT TO BE COPIED, REPRODUCED, ALTERED, OR USED BY ANYONE, OR ANY ORGANIZATION, WITHOUT THE EXPRESSED WRITTEN CONSENT OF THE ALABAMA DEPARTMENT OF TRANSPORTATION REPRESENTATIVE AUTHORIZED TO APPROVE THIS USE, ANYONE MAKING UNAUTHORIZED USE OF THIS DRAWING MAY BE PROSECUTED TO THE FULLEST EXTENT OF THE LAW.

REVISIONS .Corrected text overlap on 12-8-2021 by D.J.W.



#### ALABAMA DEPARTMENT OF TRANSPORTATION

1409 COLISEUM BOULEVARD MONTGOMERY, AL 36130-3050

DESIGN BUREAU SPECIAL DRAWING


STANDARD DETAILS FOR TRAFFIC CONTROL PLANS

Bureau Std Engr: D.J.W. SPECIAL DRAWING NO DRAWN BY:\_\_\_\_\_ SPECIAL PROJECT DETAIL DATE DRAWN: \_\_\_12-8-2021

INDEX NO







## **Authority** Alabama Airport O

Z	2 2	
REVISIO	ON HISTORY	
	55000000000	
	DESCRIPTION	DATE
PROJEC	CT INFORMATION	
DESIGN	IFD BY·	


DESIGNED BY: JNR DSG DRAWN BY DRN JNR REVIEWED BY: HZE CHK


PROJECT MANAGER DOG

1149211 SHEET TITLE:


TRAFFIC CONTROL DETAILS

ISSUE DATE










# Alabama


Ž	Z Z	Š
REVISIO	ON HISTORY	_
	DESCRIPTION	DATE
PROJEC	CT INFORMATION	
DESIGN	IED BY:	

DSG DRN CHK

DOG

TRAFFIC CONTROL DETAILS





#### BEST MANAGEMENT PRACTICES (BMP's)

TEMPORARY SLOPE DRAIN PIPE WITH ROCK DITCH CHECK AND SUMP EXCAVATION			
TEMPORARY EARTH BERM			
BRUSH BARRIER			
SILT FENCE SEDIMENT BARRIER	//		
FLOATING BASIN BOOM			
HAY BALE DITCH CHECK			
SAND BAG DITCH CHECK			
WATTLE DITCH CHECK			
SILT DIKE DITCH CHECK			
ROCK DITCH CHECK			
ROCK DITCH CHECK WITH SUMP EXCAVATION			
SILT FENCE DITCH CHECK			
WATTLE SLOPE INTERRUPTERS			

INLET PROTECTION	
STABILIZED CONSTRUCTION ENTRANCE	(SCE)
EROSION CONTROL PRODUCTS	
SLOPE DRAIN	
TEMPORARY EARTH BERM WITH POLYETHYLENE	
DREDGE, FILL	
PRIMARY STORMWATER DISCHARGE POINT	25.0
SECONDARY STORMWATER DISCHARGE POINT	25.A
BACKGROUND POINT	25.1
SEDIMENT RETENTION BARRIER	
SOLID SODDING	
TEMPORARY RIPRAP BERM	
TEMPORARY SEDIMENTATION BASIN	TSB 3
PERMANENT DETENTION BASIN	PDB 3A

#### EROSION AND SEDIMENT CONTROL PHASES

INITIAL PHASE - AS CLEARING BEGINS AND PRIOR TO ANY GRUBBING OR GRADING WORK.

INTERMEDIATE PHASE - AS NEEDED. AS WORK IS ONGOING AND ADVANCING TOWARD COMPLETION.

FINAL CONSTRUCTION - AS WORK IS COMPLETED AND PERMANENT VEGETATION IS ESTABLISHED.


#### NOTES

1. ALL FLOCCULANTS ARE TO BE APPLIED AT THE DIRECTION OF THE ENGINEER. FLOCCULANTS SHALL ONLY BE USED ON STORMWATER THAT FLOWS INTO A REQUIRED SEDIMENTATION BASIN OR FLOWS THROUGH A MINIMUM OF THREE DITCH CHECKS ABSENT OF FLOCCULANT BEFORE LEAVING THE RIGHT-OF-WAY OR DISCHARGING INTO A BLUE LINED STREAM.









# Airport Authority ERMINAL ATION AIabama

	<b>4</b>	2 12	2		
	REVISION HISTORY				
Į	Δ	DESCRIPTION	DATE		
	PROJECT INFORMATION				

DESCRIPTION DATE
PROJECT INFORMATION

DESIGNED BY:

JNR
DSG

DRAWN BY:

JNR
REVIEWED BY:

HZE
CHK

PROJECT MANAGER:
JNR
DOG

PROJECT NUMBER
1149211

SHEET TITLE:

EROSION AND SEDIMENT CONTROL PLANS LEGEND

ISSUE DATE

INDEX NO

17 August, 2023
SHEET NUMBER

20

--SPECIFICATIONS-CURRENT ALABAMA DEPARTMENT OF TRANSPORTATION

THIS DRAWING REPRESENTS DESIGNS PREPARED FOR USE BY THE ALABAMA DEPARTMENT OF TRANSPORTATION AND IS NOT TO BE COPIED, REPRODUCED, ALTERED, OR USED BY ANYONE, OR ANY ORGANIZATION, WITHOUT THE EXPRESSED WRITTEN CONSENT OF THE ALABAMA DEPARTMENT OF TRANSPORTATION REPRESENTATIVE AUTHORIZED TO APPROVE THIS USE. ANYONE MAKING UNAUTHORIZED USE OF THIS DRAWING MAY BE PROSECUTED TO THE FULLEST EXTENT OF THE LAW.

REVISIONS

DATE DRAWN: \_\_\_\_\_10-14-16




ALABAMA DEPARTMENT
OF TRANSPORTATION
1409 COLISEUM BOULEVARD
MONTGOMERY, AL 36130-3050

DESIGN BUREAU SPECIAL DRAWING

EROSION & SEDIMENT CONTROL

Bureau Std Engr: \_L.V.S.\_
DRAWN BY: \_W.D.H.\_
SPECIAL DRAWING NO
SPECIAL PROJECT DETAIL

2







08/18/2023

Alabama

DSG

DRN

CHK

DOG

MAA TERMINAL RELOCATION Mobile, Alabama

PROJECT NUMBER 1149211 SHEET TITLE:

EROSION AND SEDIMENT CONTROL - INITIAL

ISSUE DATE